## NSN 5306-01-213-3648

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-213-3648 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.902 inches **Fastener Length:** Between 2.887 inches and 2.917 inches **Head Style:** Dished hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Hole Diameter:** Between 0.070 inches and 0.080 inches **Grip Diameter:** Between 0.6230 inches and 0.6240 inches **Thread Diameter:** 0.625 inches **Grip Length:** Between 1.990 inches and 2.010 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Hole Configuration Style:** Hexagon corners Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** 

Unjf

## NSN 5306-01-213-3648

Shear Bolt - Page 2 of 2



| Specification Data | a |
|--------------------|---|
|--------------------|---|

80205-nas1310 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0