

View Online at <https://aerobasegroup.com/nsn/5306-01-213-4141>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.865 inches and 0.945 inches

**Fastener Length:**

Between 2.240 inches and 2.260 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.365 inches and 0.385 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

0.500 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.315 inches and 1.375 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

42.0 rockwell c and 46.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp 601

**Material Specification:**

Ams6304 assn standard single material response

**Surface Treatment:**

Nickel and cadmium and chromate

**Surface Treatment Specification:**

Ams2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0