

View Online at <https://aerobasegroup.com/nsn/5306-01-213-5352>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.500 inches

**Fastener Length:**

3.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.378 inches and 0.403 inches

**Width Between Flats:**

Between 0.922 inches and 0.938 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

2.000 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

11

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

23.0 rockwell c and 32.0 rockwell c

**Material:**

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1524 or steel comp 1527 or steel comp 1536 or steel comp 1541

**Material Specification:**

Sae grade 5 assn standard all material responses

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0