

View Online at <https://aerobasegroup.com/nsn/5306-01-214-2217>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.184 inches and 0.219 inches

Fastener Length:

Between 1.275 inches and 1.285 inches

Head Style:

Dee

Head Diameter:

0.175 inches

Head Height:

0.120 inches

Distance From Centerline To Flat:

Between 0.264 inches and 0.274 inches

Shank Unthreaded Hole Diameter:

0.076 inches and 0.086 inches first hole

First Diameter From Head:

Between 0.311 inches and 0.312 inches

Second Diameter From Head:

Between 0.181 inches and 0.191 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.965 inches and 0.975 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.066 inches and 1.091 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.155 inches and 1.175 inches first hole

Externally Relieved Body Diameter Quantity:

2

Special Features:

Dee undercut head

Material:

Steel uns k23080

Material Specification:

Ams 6411 assn standard single material response

Surface Treatment:

Chromium

Surface Treatment Specification:

Ps13102 cl b, fscm 76301 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0