## NSN 5306-01-214-2759

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-214-2759 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.738 inches **Fastener Length:** Between 1.648 inches and 1.668 inches **Head Style:** Round w/wrench flats chamfered **Head Diameter:** Between 0.450 inches and 0.470 inches **Head Height:** Between 0.075 inches and 0.085 inches Width Between Flats: Between 0.320 inches and 0.340 inches First Diameter From Head: Between 0.258 inches and 0.260 inches **Second Diameter From Head:** Between 0.215 inches and 0.225 inches **Third Diameter From Head:** Between 0.258 inches and 0.260 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.290 inches and 0.310 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.560 inches and 0.580 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.910 inches and 0.930 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 **Special Features:** 3 pins equally spaced and key on top of head Material: Nickel alloy **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-01-214-2759

Externally Relieved Body Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0