Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-214-5044

Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.547 inches and 0.597 inches Fastener Length: Between 2.119 inches and 2.149 inches **Head Style:** Hexagon **Head Height:** Between 0.375 inches and 0.390 inches Width Between Flats: Between 1.052 inches and 1.064 inches **Shank Unthreaded Hole Diameter:** 0.141 inches and 0.151 inches first hole **Concentric Hole Diameter:** Between 0.437 inches and 0.444 inches **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 16 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.981 inches and 2.031 inches first hole **Special Features:** Sftt and stdc also apply to inside, finish code306 (white) Material: Titanium alloy **Material Specification:** Ams4967 assn standard single material response or ams4928 assn standard single material response Surface Treatment: Paint head **Surface Treatment Specification:** Fs-595 federal standard single treatment response head Style Designator: Concentric hole unthreaded **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure:

NSN 5306-01-214-5044

Internally Relieved Body Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

