

View Online at <https://aerobasegroup.com/nsn/5306-01-214-5044>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.547 inches and 0.597 inches

Fastener Length:

Between 2.119 inches and 2.149 inches

Head Style:

Hexagon

Head Height:

Between 0.375 inches and 0.390 inches

Width Between Flats:

Between 1.052 inches and 1.064 inches

Shank Unthreaded Hole Diameter:

0.141 inches and 0.151 inches first hole

Concentric Hole Diameter:

Between 0.437 inches and 0.444 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.981 inches and 2.031 inches first hole

Special Features:

Sftt and stdc also apply to inside, finish code306 (white)

Material:

Titanium alloy

Material Specification:

Ams4967 assn standard single material response or ams4928 assn standard single material response

Surface Treatment:

Paint head

Surface Treatment Specification:

Fs-595 federal standard single treatment response head

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0