## NSN 5306-01-215-2507

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-215-2507 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.420 inches and 0.440 inches **Fastener Length:** Between 1.656 inches and 1.676 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **First Diameter From Head:** 0.249 inches **Second Diameter From Head:** Between 0.200 inches and 0.205 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.260 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.956 inches and 1.036 inches **Thread Diameter:** 0.250 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Nickel alloy 718 **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5306-01-215-2507

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0