NSN 5306-01-215-2515

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-215-2515 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.630 inches and 0.660 inches **Fastener Length:** Between 1.010 inches and 1.030 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.070 inches and 0.080 inches first hole **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.370 inches and 0.380 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 0.780 inches first hole **Surface Finish:** 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** C50tf13 cl-b fscm 07482 mfr ref single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5306-01-215-2515

Close Tolerance Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0