

View Online at <https://aerobasegroup.com/nsn/5306-01-215-3999>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.450 inches and 0.480 inches

**Fastener Length:**

Between 1.767 inches and 1.787 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.240 inches and 0.260 inches

**Width Between Flats:**

Between 0.679 inches and 0.690 inches

**Hole Diameter:**

Between 0.060 inches and 0.080 inches

**Grip Diameter:**

Between 0.4365 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.094 inches and 0.102 inches first hole

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.307 inches and 1.317 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.627 inches first hole

**Surface Finish:**

63.0 microinches bearing surface of head

**Material:**

Nickel alloy 718

**Material Specification:**

C50tf13 cl-b, fscm 07482 mfr ref single material response

**Precious Material And Location:**

silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams2411 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0