NSN 5306-01-215-5175

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-215-5175 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.247 inches **Fastener Length:** Between 0.449 inches and 0.459 inches **Head Diameter:** 0.320 inches **Head Height:** 0.161 inches **Extended Washer Diameter:** 0.500 inches **Extended Washer Thickness:** 0.060 inches **Hole Diameter:** Between 0.044 inches and 0.049 inches **First Diameter From Head:** Between 0.196 inches and 0.206 inches **Second Diameter From Head:** Between 0.118 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.063 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.449 inches and 0.459 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.156 inches and 0.158 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 **Hardness Rating:**

30.0 rockwell c and 45.0 rockwell c

Hole Configuration Style:

Round internal hexagon

NSN 5306-01-215-5175

Internal Wrenching Bolt - Page 2 of 2



Externally Relieved Body Diameter Quantity:
2
Material:
Steel comp 410
Material Specification:
Qq-s-763 federal specification single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0