

View Online at <https://aerobasegroup.com/nsn/5306-01-215-5175>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.247 inches

**Fastener Length:**

Between 0.449 inches and 0.459 inches

**Head Diameter:**

0.320 inches

**Head Height:**

0.161 inches

**Extended Washer Diameter:**

0.500 inches

**Extended Washer Thickness:**

0.060 inches

**Hole Diameter:**

Between 0.044 inches and 0.049 inches

**First Diameter From Head:**

Between 0.196 inches and 0.206 inches

**Second Diameter From Head:**

Between 0.118 inches and 0.120 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.063 inches and 0.078 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.449 inches and 0.459 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

Between 0.156 inches and 0.158 inches

**Hole Quantity:**

2

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

30.0 rockwell c and 45.0 rockwell c

**Hole Configuration Style:**

Round internal hexagon

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 410

**Material Specification:**

Qq-s-763 federal specification single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0