

View Online at <https://aerobasegroup.com/nsn/5306-01-215-5299>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.415 inches and 0.445 inches

**Fastener Length:**

Between 0.858 inches and 0.878 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.293 inches and 0.313 inches

**Width Between Flats:**

0.312 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

**Shoulder Diameter:**

0.249 inches and 0.250 inches first shoulder

**Shoulder Length:**

0.433 inches and 0.443 inches first shoulder

**Hole Diameter:**

Between 0.075 inches and 0.095 inches

**Thread Diameter:**

0.190 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

24.0 rockwell c and 35.0 rockwell c

**Minimum Yield Strength:**

85000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5731 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0