## NSN 5306-01-215-5323

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-215-5323

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.443 inches and 0.493 inches
Fastener Length:
Between 1.578 inches and 1.608 inches
Head Style:
Spline extended washer
Head Height:
Between 0.194 inches and 0.234 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
Between 0.026 inches and 0.046 inches
Hole Diameter:
Between 0.076 inches and 0.081 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.081 inches first hole
Head Minor Diameter:
Between 0.423 inches and 0.438 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
180000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.386 inches first hole and 1.426 inches first hole
Material:
Nickel alloy

## NSN 5306-01-215-5323

Shear Bolt - Page 2 of 2



Surrace	reatment

Chromium

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0