NSN 5306-01-215-5324

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-215-5324

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.589 inches and 0.639 inches **Fastener Length:** Between 1.974 inches and 2.004 inches **Head Style:** Spline extended washer **Head Height:** Between 0.263 inches and 0.303 inches Width Between Flats: Between 0.423 inches and 0.438 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5306-01-215-5324

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0