

View Online at <https://aerobasegroup.com/nsn/5306-01-215-5334>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.360 inches and 0.420 inches

Fastener Length:

Between 2.560 inches and 2.590 inches

Head Style:

Hexagon

Head Height:

Between 0.115 inches and 0.135 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.052 inches and 0.058 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 2.170 inches and 2.200 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.390 inches and 2.420 inches first hole

Surface Finish:

32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0