NSN 5306-01-216-3993



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-216-3993 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.000 inches and 1.188 inches **Fastener Length:** Between 3.440 inches and 3.500 inches **Head Style:** Distorted head **Head Height:** Between 0.250 inches and 0.260 inches Width Between Flats: Between 0.551 inches and 0.563 inches

Locking Feature:
Distortions top of head

Thread Diameter:

0.375 inches

Features Provided:

Finished head

16

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Material:

Steel

Material Specification:

Sae, gr8 assn standard all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

G-4341-m, code 20u32 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5306-01-216-3993

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0