## NSN 5306-01-216-4348

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-216-4348 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.669 inches and 0.699 inches **Fastener Length:** Between 0.830 inches and 0.850 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.373 inches and 0.393 inches Width Between Flats: 0.438 inches **Extended Washer Diameter:** Between 0.552 inches and 0.572 inches **Extended Washer Thickness:** Between 0.090 inches and 0.100 inches **Hole Diameter:** Between 0.060 inches and 0.080 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.151 inches and 0.161 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Double hexagon flats **Surface Finish:** 32.0 microinches threads Material: Nickel alloy 718 **Material Specification:** C50tf13 cl-b fscm 07482 mfr ref single material response

Unjf

**Thread Series Designator:** 

## NSN 5306-01-216-4348

Close Tolerance Bolt - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0