

View Online at <https://aerobasegroup.com/nsn/5306-01-217-2912>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.400 inches and 0.450 inches

**Fastener Length:**

Between 0.972 inches and 1.002 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.429 inches and 0.439 inches

**Shoulder Diameter:**

0.2490 inches and 0.2495 inches first shoulder

**Shoulder Length:**

0.552 inches and 0.572 inches first shoulder

**Hole Diameter:**

Between 0.046 inches and 0.056 inches

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Hexagon corners

**Shoulder Shape:**

Round first shoulder

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6704 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0