NSN 5306-01-217-5160



Machine Bolt - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5306-01-217-5160
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.740 inches and 0.820 inches
Fastener Length:
Between 1.678 inches and 1.698 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.320 inches and 0.340 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.420 inches and 0.440 inches
Extended Washer Thickness:
Between 0.060 inches and 0.070 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.878 inches and 0.938 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Surface Finish:
63.0 microinches grip
Material:
Steel comp 8740
Material Specification:

Ams6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams2400 assn standard single treatment response

Thread Series Designator:

Unf

NSN 5306-01-217-5160

Machine Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0