

View Online at <https://aerobasegroup.com/nsn/5306-01-217-9055>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.745 inches and 0.792 inches

**Fastener Length:**

Between 2.183 inches and 2.230 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.340 inches and 0.360 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.136 inches and 0.146 inches first hole

**Thread Diameter:**

0.625 inches

**Grip Length:**

1.438 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.976 inches and 2.008 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium or cadmium and chromate

**Surface Treatment Specification:**

Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 cl 2 military specification 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.