

View Online at <https://aerobasegroup.com/nsn/5306-01-218-0908>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.451 inches and 0.511 inches

**Fastener Length:**

Between 0.966 inches and 0.996 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.109 inches and 0.141 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Washer Quantity:**

1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Primary Washer Outside Diameter:**

0.420 inches

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

0.020 inches

**Special Features:**

Bolt furnished with tab and spacer; tab cres comp 301 per mil-s-5059; spacer cres type 303se per astm a582

**Material:**

Steel comp 301 primary washer

**Material Specification:**

Mil-s-5059 military specification single material response primary washer

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.