

View Online at <https://aerobasegroup.com/nsn/5306-01-218-0910>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.633 inches and 0.693 inches

Fastener Length:

Between 2.898 inches and 2.928 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Washer Quantity:

1

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

140000 pounds per square inch

Primary Washer Outside Diameter:

0.600 inches

Primary Washer Style:

Finishing

Primary Washer Material Thickness:

0.032 inches

Special Features:

Bolt furnished with tab and spacer; tab cres comp 301 per mil-s-5059; spacer cres type 303se per astm a582

Material:

Steel comp 301 primary washer

Material Specification:

Mil-s-5059 military specification single material response primary washer

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.