## NSN 5306-01-218-3133

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-218-3133 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.443 inches and 0.493 inches **Fastener Length:** Between 1.515 inches and 1.545 inches **Head Style:** Spline extended washer **Head Height:** Between 0.194 inches and 0.234 inches **Extended Washer Diameter:** Between 0.460 inches and 0.470 inches **Extended Washer Thickness:** Between 0.026 inches and 0.046 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Head Minor Diameter:** Between 0.318 inches and 0.324 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5306-01-218-3133

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0