NSN 5306-01-218-7522

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-218-7522 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.824 inches and 0.874 inches **Fastener Length:** Between 4.896 inches and 4.926 inches **Head Style:** Spline extended washer **Head Height:** Between 0.414 inches and 0.434 inches **Extended Washer Diameter:** Between 1.037 inches and 1.047 inches **Extended Washer Thickness:** Between 0.071 inches and 0.091 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Head Minor Diameter:** Between 0.711 inches and 0.717 inches **End Application:** Aircraft, c-2a (reprocured); aircraft, hornet f/a-18 **Thread Diameter:** 0.562 inches **Grip Length:** Between 4.052 inches and 4.072 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Special Features:** Finish electropolished Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-218-7522

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0