## NSN 5306-01-219-2955

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-219-2955 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.180 inches **Fastener Length:** 2.500 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.390 inches Width Between Flats: Between 0.611 inches and 0.627 inches **Extended Washer Diameter:** 0.714 inches **Extended Washer Thickness:** Between 0.120 inches and 0.140 inches **First Diameter From Head:** Between 0.413 inches and 0.423 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.320 inches **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 8637 or steel comp 8640 **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Phosphate zinc **Surface Treatment Specification:** Jdt826, fsc-75160 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life:

She N/a

## NSN 5306-01-219-2955

Externally Relieved Body Bolt - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A003b0