## NSN 5306-01-219-7157

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-219-7157						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.444 inches and 0.494 inches						
Fastener Length:						
Between 1.016 inches and 1.046 inches						
Head Style:						
Dished hexagon						
Head Height:						
Between 0.156 inches and 0.171 inches						
Width Between Flats:						
Between 0.492 inches and 0.502 inches						
Locking Feature:						
Patch threads						
Grip Diameter:						
Between 0.3110 inches and 0.3120 inches						
Thread Diameter:						
0.312 inches						
Grip Length:						
Between 0.552 inches and 0.572 inches						
Thready Qty Per Inch (tpi):						
24						
Min. Tensile Strength (psi):						
160000 pounds per square inch						
Hardness Rating:						
36.0 rockwell c and 40.0 rockwell c						
Surface Finish:						
32.0 microinches threads						
Material:						
Plastic polyamide locking feature						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416, type 2 class 2 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Specification Data:						
80205-nas1225 professional/industrial association standard						
Shelf Life:						

N/a

## NSN 5306-01-219-7157

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0