

View Online at <https://aerobasegroup.com/nsn/5306-01-219-9121>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.526 inches and 0.576 inches

Fastener Length:

Between 1.723 inches and 1.753 inches

Head Style:

Spline extended washer

Head Height:

Between 0.247 inches and 0.287 inches

Width Between Flats:

Between 0.383 inches and 0.389 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

Between 0.035 inches and 0.055 inches

Grip Diameter:

Between 0.3115 inches and 0.3120 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 1.177 inches and 1.197 inches

Thready Qty Per Inch (tpi):

24

Special Features:

Thd hole in top of head 0.138-32 unjc-3b thd; injection port 0.120 in. Lg, 0.060 in. Wide in unthd shank; distance from head to beginning of injection port 0.760 in.

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0