# NSN 5306-01-219-9123

Close Tolerance Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-219-9123



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.526 inches and 0.576 inches

#### Fastener Length:

Between 1.848 inches and 1.878 inches

#### Head Style:

Spline extended washer

# Head Height:

Between 0.247 inches and 0.287 inches

# Width Between Flats:

Between 0.383 inches and 0.389 inches

#### **Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

#### **Extended Washer Thickness:**

Between 0.035 inches and 0.055 inches

#### **Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

# **Thread Diameter:**

0.312 inches

Grip Length:

Between 1.302 inches and 1.322 inches

# Thready Qty Per Inch (tpi):

24

# **Special Features:**

Thd hole in top of head 0.138-32 unjc-3b thd, injection port 0.120 in. Lg, 0.060 in. Wide in unthd shank; distance from head to beginning of injection port 0.860 in.

#### Material:

Steel comp xm-13

# **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5306-01-219-9123

Close Tolerance Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

