NSN 5306-01-220-0179

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-220-0179

Through Observ
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.553 inches and 0.603 inches
Fastener Length:
Between 1.688 inches and 1.718 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Shoulder Diameter:
0.3891 inches and 0.3901 inches first shoulder
Shoulder Length:
1.115 inches and 1.135 inches first shoulder
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas2906 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-220-0179

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0