

View Online at <https://aerobasegroup.com/nsn/5306-01-220-8667>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.740 inches and 0.800 inches

Fastener Length:

Between 2.822 inches and 2.862 inches

Head Style:

Dished hexagon

Head Height:

Between 0.328 inches and 0.360 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Shoulder Diameter:

0.620 inches and 0.624 inches first shoulder

Shoulder Length:

2.062 inches and 2.082 inches first shoulder

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

125000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1297 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0