

View Online at <https://aerobasegroup.com/nsn/5306-01-220-8668>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.732 inches and 0.815 inches

**Fastener Length:**

Between 1.887 inches and 1.917 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.312 inches and 0.327 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Shoulder Diameter:**

0.6235 inches and 0.6240 inches first shoulder

**Shoulder Length:**

1.052 inches and 1.072 inches first shoulder

**Thread Diameter:**

0.562 inches

**Thready Qty Per Inch (tpi):**

18

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Dry film lubed shoulder. Undercut below shoulder 0.050 inch min, 0.083 inch maximum length

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0