

View Online at <https://aerobasegroup.com/nsn/5306-01-220-8674>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.368 inches and 0.418 inches

**Fastener Length:**

Between 1.128 inches and 1.158 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.195 inches and 0.215 inches

**Extended Washer Diameter:**

Between 0.349 inches and 0.359 inches

**Extended Washer Thickness:**

Between 0.017 inches and 0.037 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Head Minor Diameter:**

Between 0.253 inches and 0.259 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0