

View Online at <https://aerobasegroup.com/nsn/5306-01-220-8679>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.444 inches and 0.494 inches

**Fastener Length:**

Between 2.892 inches and 2.922 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.156 inches and 0.171 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 2.428 inches and 2.448 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1305 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0