

View Online at <https://aerobasegroup.com/nsn/5306-01-221-8689>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.958 inches and 1.000 inches

**Fastener Length:**

Between 2.280 inches and 2.312 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.608 inches and 0.628 inches

**Width Between Flats:**

0.6875 inches

**Extended Washer Diameter:**

Between 1.040 inches and 1.050 inches

**Extended Washer Thickness:**

Between 0.140 inches and 0.160 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 1.312 inches and 1.322 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Casehardened

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-8844 cl 1 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Ams 2401-3 assn standard 1st treatment response and qq-p-416, type 2 federal specification 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-8844 spec.