## NSN 5306-01-221-9203

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-221-9203

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.234 inches  |
| Fastener Length:  |
| Between 1.063 inches and 1.094 inches                                   |
| Head Style:   |
| Pan no. 2   |
| Head Diameter:  |
| Between 0.218 inches and 0.226 inches                                   |
| Head Height:  |
| Between 0.134 inches and 0.138 inches                                   |
| First Diameter From Head:   |
| 0.094 inches  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.860 inches  |
| Internal Drive Style:   |
| Hexagon   |
| End Application:  |
| An/alq-131 block 1  |
| Thread Diameter:  |
| 0.138 inches  |
| Width Across Flats:   |
| Between 0.1094 inches and 0.1111 inches                                 |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Externally Relieved Body Diameter Quantity:                             |
| 1   |
| Special Features:   |
| Externally relieved portion has asleeving per mil-i-23053 cl 1 white    |
| Material:   |
| Iron alloy 660  |
| Material Specification:   |
| Ams 5731 assn standard single material response                         |
| Surface Treatment:  |
| Passivate   |
| Surface Treatment Specification:  |
| Qq-p-35 type 2 federal specification single treatment response          |
| Thread Series Designator:   |
| Unrc  |

## NSN 5306-01-221-9203

Internal Wrenching Bolt - Page 2 of 2



| _  |    |    |     |      |  |
|----|----|----|-----|------|--|
| CI | ~~ | 14 | I i | ife: |  |
| J. | 16 |    |     | HE.  |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0