NSN 5306-01-223-2060

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-223-2060 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.558 inches and 0.588 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.2016 inches and 0.2026 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 or steel comp 4340 **Material Specification:** -1I-s-5000 military specification 1st material response and -1I-s-6049 military specification 2nd material response or ams6322 military specification 2nd material response and mil-s-5000 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type2 class2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5306-01-223-2060

Shear Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.