

View Online at <https://aerobasegroup.com/nsn/5306-01-224-1738>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.528 inches

**Fastener Length:**

Between 6.450 inches and 6.480 inches

**Head Style:**

Undercut hexagon

**Head Height:**

Between 0.250 inches and 0.265 inches

**Width Between Flats:**

0.836 inches

**Grip Diameter:**

Between 0.4945 inches and 0.4950 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches and 0.151 inches first hole

**Thread Diameter:**

0.5000 inches

**Grip Length:**

Between 5.927 inches and 5.947 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

1600000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

6.267 inches all holes

**Material:**

Steel

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6208-95d professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0