## NSN 5306-01-225-5206

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-225-5206

view Offilitie at Tittps://aerobasegroup.com/fish/3300-01-223-3200
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.449 inches and 0.459 inches
Fastener Length:
Between 1.689 inches and 1.719 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.689 inches and 1.719 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6206-20dh professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-01-225-5206

Shear Bolt - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.