## NSN 5306-01-225-7720

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-225-7720

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.618 inches and 0.668 inches
Fastener Length:
Between 2.378 inches and 2.408 inches
Head Style:
Double hexagon w/hole
Head Height:
0.322 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
0.091 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3740 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.740 inches and 1.760 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Hole Configuration Style:

Material:

Steel comp xm-13

**Material Specification:** 

Double hexagon longitudinal hole

Ams5629 assn standard single material response

## NSN 5306-01-225-7720

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: