# NSN 5306-01-225-7720

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-225-7720



# Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.618 inches and 0.668 inches

## Fastener Length:

Between 2.378 inches and 2.408 inches

#### Head Style:

Double hexagon w/hole

## **Head Height:**

0.322 inches

## Width Between Flats:

Between 0.430 inches and 0.439 inches

## **Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

## **Extended Washer Thickness:**

0.091 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

## **Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

## **Thread Diameter:**

0.375 inches

## Grip Length:

Between 1.740 inches and 1.760 inches

## Hole Quantity:

4

Hole Type:

Drilled

# Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

220000 pounds per square inch

# Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

# Hole Configuration Style:

Double hexagon longitudinal hole

Material:

Steel comp xm-13

# Material Specification:

Ams5629 assn standard single material response

# NSN 5306-01-225-7720

Shear Bolt - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0