NSN 5306-01-225-8038

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-225-8038 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 1.090 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.204 inches Width Between Flats: Between 0.490 inches and 0.502 inches **First Diameter From Head:** Between 0.285 inches and 0.290 inches **Second Diameter From Head:** 0.312 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.190 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.710 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5306-01-225-8038

Externally Relieved Body Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.