

View Online at <https://aerobasegroup.com/nsn/5306-01-225-8038>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.380 inches

**Fastener Length:**

1.090 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.204 inches

**Width Between Flats:**

Between 0.490 inches and 0.502 inches

**First Diameter From Head:**

Between 0.285 inches and 0.290 inches

**Second Diameter From Head:**

0.312 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.190 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.710 inches

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-18732 spec.