Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-225-8038

| view Online at https://aerobasegroup.com/hsh/5506-01-225-8038 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.380 inches |
| Fastener Length: |
| 1.090 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.172 inches and 0.204 inches |
| Width Between Flats: |
| Between 0.490 inches and 0.502 inches |
| First Diameter From Head: |
| Between 0.285 inches and 0.290 inches |
| Second Diameter From Head: |
| 0.312 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.190 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.710 inches |
| Thread Diameter: |
| 0.312 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 431 |
| Material Specification: |
| Mil-s-18732 military specification single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |

NSN 5306-01-225-8038

Externally Relieved Body Bolt - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.