## NSN 5306-01-225-9645

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-225-9645

view Online at https://aerobasegroup.com/nish/3300-01-223-9043
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.815 inches and 0.865 inches
Fastener Length:
Between 3.825 inches and 3.855 inches
Head Style:
Dished hexagon
Head Height:
Between 0.281 inches and 0.296 inches
Width Between Flats:
Between 0.865 inches and 0.877 inches
Grip Diameter:
Between 0.5761 inches and 0.5771 inches
Thread Diameter:
0.562 inches
Grip Length:
Between 2.990 inches and 3.010 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
63.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas2909 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>

--

## NSN 5306-01-225-9645

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0