NSN 5306-01-226-8665

Assembled Washer Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-226-8665



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.451 inches and 0.511 inches Fastener Length: Between 0.841 inches and 0.871 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.367 inches and 0.376 inches Washer Quantity: 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch **Primary Washer Outside Diameter:** 0.420 inches **Primary Washer Style:** Finishing

Primary Washer Material Thickness:

0.020 inches

Special Features:

Bolt furnished with tab: cres comp 301 per mil-s-5059, passivated per qq-p-35

Material:

Steel comp 303se stand-off

Material Specification:

Mil-s-5059 military specification single material response primary washer

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-226-8665

Assembled Washer Bolt - Page 2 of 2

AeroBase Group

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.