## NSN 5306-01-228-6796

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-228-6796

Thread Class:		
3a		
Thread Direction:		
Right-hand		
Thread Length:		
1.001 inches		
Fastener Length:		
Between 1.611 inches and 1.641 inches		
Head Style:		
Double hexagon w/hole		
Head Height:		
0.618 inches		
Width Between Flats:		
Between 0.682 inches and 0.691 inches		
Extended Washer Diameter:		
Between 1.040 inches and 1.050 inches		
Extended Washer Thickness:		
0.150 inches		
Hole Diameter:		
Between 0.050 inches and 0.060 inches		
Grip Diameter:		
Between 0.6230 inches and 0.6240 inches		
Thread Diameter:		
0.625 inches		
Grip Length:		
Between 0.615 inches and 0.635 inches		
Hole Quantity:		
4		
Hole Type:		
Drilled		
Thready Qty Per Inch (tpi):		
18		
Min. Tensile Strength (psi):		
200000 pounds per square inch		
Hole Configuration Style:		
Double hexagon longitudinal hole		

Material:

Iron alloy 660

**Material Specification:** 

Ams5737 assn standard single material response

**Surface Treatment:** 

Cadmium

## NSN 5306-01-228-6796

Shear Bolt - Page 2 of 2



Surface	Treatment	Specification:
Juliace	HEAUHEIL	opecilication.

Qq-p-416, type 1, cl 3 or type 2, cl 3 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0