## NSN 5306-01-229-3480

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-229-3480

Qq-p-416, type 2, class 2 federal specification single treatment response

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 2.688 inches and 2.721 inches
Fastener Length:
Between 2.750 inches and 2.752 inches
Head Style:
Crowned hexagon
Head Height:
0.172 inches
Width Between Flats:
Between 0.490 inches and 0.502 inches
Hole Diameter:
Between 0.069 inches and 0.074 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.031 inches and 0.062 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Special Features:
Adjusting slot thread end
Material:
Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

## **NSN 5306-01-229-3480** Machine Bolt - Page 2 of 2

A003b0



Thread Series Designator:
Unf
Specification Data:
80205-nas428 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: