## NSN 5306-01-229-9964

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-229-9964 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 2.948 inches and 2.978 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Unthreaded Hole Diameter:** 0.070 inches and 0.080 inches first hole **Thread Diameter:** 0.190 inches **Grip Length:** Between 2.615 inches and 2.635 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 2.775 inches and 2.825 inches first hole **Surface Finish:** 63.0 microinches grip Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas673 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-229-9964

Close Tolerance Bolt - Page 2 of 2



Fiig:

A003b0