## NSN 5306-01-230-2440

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-230-2440 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.309 inches and 0.360 inches **Fastener Length:** Between 2.570 inches and 2.590 inches **Head Style:** Dished hexagon **Head Height:** Between 0.126 inches and 0.141 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.086 inches first hole **Thread Diameter:** 0.250 inches **Grip Length:** Between 2.125 inches and 2.141 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.385 inches and 2.415 inches first hole **Surface Finish:** 63.0 microinches grip **Special Features:** Furnish with retaining element, drill 2 holes 90 degree apart Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5306-01-230-2440

Close Tolerance Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0